

# Product Technical Data Sheet - Supaflex Braided Cable Sleeving



## Description

Supaflex Braided Cable Sleeving is suitable for the enclosure and protection of cables and hoses. It can be used for many types of electrical and mechanical installations, including power, telecommunications, automotive, marine, aircraft and domestic appliances. The woven design enables any number of cables to branch out along the assembly. It is easy to use and available in a wide range of sizes. For best results cut with a hot knife or soldering iron to seal the ends and prevent fraying.

## Specification

Material: Polyester  
 Standard Colours: Black and Grey  
 Flammability: Self-extinguishing to UL224 VW1  
 Work Temperature: -50°C to +150°C  
 Melting Point: 230°C (± 5°C)  
 Standards: Low Smoke, Halogen Free

Partex Part Number	Nominal Diameter (mm)	Size Range (mm)		Standard Pack Qty (M)
		Minimum	Maximum	
<b>SUP4</b>	4	2	7	10, 100
<b>SUP6</b>	6	4	11	10, 100
<b>SUP8</b>	8	5	12	10, 100
<b>SUP10</b>	10	7	15	10, 100
<b>SUP12</b>	12	8	17	10, 100
<b>SUP15</b>	15	10	21	10, 100
<b>SUP20</b>	20	14	27	10, 100
<b>SUP25</b>	25	18	34	10, 100
<b>SUP30</b>	30	28	47	10, 100
<b>SUP40</b>	40	35	64	10, 100
<b>SUP50</b>	50	45	75	10, 100

**Partex Marking Systems (UK) LTD**

**61-64 Station Road, Coleshill, Birmingham B46 1JT**

**Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk**