

Product Technical Data Sheet:

Coloured Cable Ties

Description

Partex offer a wide range of coloured cable ties.
Available in Red, Blue, Green, Brown and Yellow (specify colour when ordering).



Specification

Material: DuPont Zytel 101F Nylon 6.6 Polyamide
Flammability: Self-extinguishing to UL 94-V2
Work Temperature: - 40°C to +85°C
Recommended storage conditions: +15°C to +30°C 50% Humidity.

High tension, highly resistant against; Brake Fluids, Lubricants, Power Steering Fluids, Oil, Grease, Paints, Lacquer Detergents, Animal and Vegetable Fats, Alkali up to 40% and Gasoline.

Partex Part No	Length (mm)	Width (mm)	Maximum Bundle (mm)	Tensile Strength (kg)
HFC100	100	2.5	18	8
HFC140	140	3.6	33	18
HFC200L	200	2.5	50	8
HFC200	200	4.8	50	22
HFC300	300	4.8	76	22

Silver Cable Ties

Ideal for securing wheel trims.



Partex Part No	Length (mm)	Width (mm)	Maximum Bundle (mm)	Tensile Strength (kg)
HFC300 SIL	300	4.8	76	22
HFC365 SIL	370	4.8	102	22

Partex Marking Systems (UK) LTD

61-64 Station Road, Coleshill, Birmingham B46 1JT

Tel: 01675 463670 Fax: 01675 463520 Email: sales@partex.co.uk