

PWT Wrap-around label

- Self-laminating labels for marking of wires, cables, and hoses
- Designed for printing on MK10 thermal transfer printers
- Matte finish material with permanent acrylic adhesive
- Excellent resistance to alcohols



BENEFITS

PWT is a self-laminating and printable wrap-around label. It is primarily designed for marking wires, cables and hoses. It's highly durable, made from UL-approved MT310 polyester. It can be used both indoors and outdoors. The print area is protected by the transparent part when it is wrapped around the cable.

The labels are printed using MK10-series thermal transfer printers and designed in the Promark Creator software.

TECHNICAL INFORMATION

Material

UL approved MT310 transparent polyester with matte surface.

Adhesive

Permanent acrylic

Temperature range

Service temperature: -40°C to +150°C

Minimum application: +10°C

Resistance properties

UL code PGGU2.

UV resistant

Excellent resistance to isopropyl alcohol, oil and water.

Colours

Standard: Yellow, white.

Expiry date and storage

Storage stability: Two years stored at +21°C and 50% relative humidity (RH).

Printing

Printable with recommended thermal transfer printers from the MK10 series (e.g. EOS, SQUIX). Use Promark Creator software for design and production management.

Recommended ribbon

MK10-RB-5095



PRODUCT SIZE AND PACKAGING

Delivery unit: Roll, three tracks of labels.

Article		Label size				Printable surface				Label quantity [pcs]
Yellow	White	W [mm]	H [mm]	W [inch]	H [inch]	W [mm]	H [mm]	W [inch]	H [inch]	
PWT1711033*4SM	PWT1711033*9SM	17.8	33.9	0.701	1.335	16	13	0.603	0.512	3000
PWT2316055D4SM	PWT2316055*9SM	23	55	0.906	2.165	21	16	0.827	0.630	2400
PWT2514035*4SM	PWT2514035*9SM	25	35	0.984	1.378	24	14	0.944	0.551	4500
PWT2519076*4SM	PWT2519076*9SM	25	76	0.984	2.992	23	19	0.906	0.748	1800
PWT2525140D4SM	PWT2525140*9SM	25	140	0.984	5.552	24	25	0.944	0.984	1050
PWT3225093*4SM	PWT3225093D4SM	32	93	1.260	3.661	30	25	1.181	0.984	1500

*) Core diameter (D=38mm, B=76mm)

CABLE DIAMETER

Delivery unit: Roll, three tracks of labels.

Article		Cable diameter			
Yellow	White	Min [mm]	Max [mm]	Min [inch]	Max [inch]
PWT1711033*4SM	PWT1711033*9SM	3.5	5.7	0.138	0.224
PWT2316055D4SM	PWT2316055*9SM	5.1	10.8	0.201	0.425
PWT2514035*4SM	PWT2514035*9SM	4.5	5.1	0.177	0.201
PWT2519076*4SM	PWT2519076*9SM	6.0	16.6	0.236	0.654
PWT2525140D4SM	PWT2525140*9SM	8.0	35.0	0.315	1.378
PWT3225093*4SM	PWT3225093D4SM	8.0	20.1	0.315	0.791

*) Core diameter (D=38mm, B=76mm)

RELATED PRODUCTS



MK10 printers

