

## PWT Wrap-around label

- Self-laminating labels for marking of wires, cables, and hoses
- Designed for printing on MK10 thermal transfer printers
- Matte finish material with permanent acrylic adhesive
- Excellent resistance to alcohols



### BENEFITS

PWT is a self-laminating and printable wrap-around label. It is primarily designed for marking wires, cables and hoses. It's highly durable, made from UL-approved MT310 polyester. It can be used both indoors and outdoors. The print area is protected by the transparent part when it is wrapped around the cable.

The labels are printed using MK10-series thermal transfer printers and designed in the Promark Creator software.

### TECHNICAL INFORMATION

#### Material

UL approved MT310 transparent polyester with matte surface.

#### Adhesive

Permanent acrylic

#### Temperature range

Service temperature:  $-40^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$

Minimum application:  $+10^{\circ}\text{C}$

#### Resistance properties

UL code PGGU2.

UV resistant

Excellent resistance to isopropyl alcohol, oil and water.

#### Colours

Standard: Yellow, white.

#### Expiry date and storage

Storage stability: Two years stored at  $+21^{\circ}\text{C}$  and 50% relative humidity (RH).

#### Printing

Printable with recommended thermal transfer printers from the MK10 series (e.g. EOS, SQUIX). Use Promark Creator software for design and production management.

#### Recommended ribbon

MK10-RB-5095



## PRODUCT SIZE AND PACKAGING

Delivery unit: Roll, three tracks of labels.

| Article        |                | Label size |        |          |          | Printable surface |        |          |          | Label quantity [pcs] |
|----------------|----------------|------------|--------|----------|----------|-------------------|--------|----------|----------|----------------------|
| Yellow         | White          | W [mm]     | H [mm] | W [inch] | H [inch] | W [mm]            | H [mm] | W [inch] | H [inch] |                      |
| PWT1711033*4SM | PWT1711033*9SM | 17.8       | 33.9   | 0.701    | 1.335    | 16                | 13     | 0.603    | 0.512    | 3000                 |
| PWT2316055D4SM | PWT2316055*9SM | 23         | 55     | 0.906    | 2.165    | 21                | 16     | 0.827    | 0.630    | 2400                 |
| PWT2514035*4SM | PWT2514035*9SM | 25         | 35     | 0.984    | 1.378    | 24                | 14     | 0.944    | 0.551    | 4500                 |
| PWT2519076*4SM | PWT2519076*9SM | 25         | 76     | 0.984    | 2.992    | 23                | 19     | 0.906    | 0.748    | 1800                 |
| PWT2525140D4SM | PWT2525140*9SM | 25         | 140    | 0.984    | 5.552    | 24                | 25     | 0.944    | 0.984    | 1050                 |
| PWT3225093*4SM | PWT3225093D4SM | 32         | 93     | 1.260    | 3.661    | 30                | 25     | 1.181    | 0.984    | 1500                 |

\*) Core diameter (D=38mm, B=76mm)

## CABLE DIAMETER

Delivery unit: Roll, three tracks of labels.

| Article        |                | Cable diameter |          |            |            |
|----------------|----------------|----------------|----------|------------|------------|
| Yellow         | White          | Min [mm]       | Max [mm] | Min [inch] | Max [inch] |
| PWT1711033*4SM | PWT1711033*9SM | 3.5            | 5.7      | 0.138      | 0.224      |
| PWT2316055D4SM | PWT2316055*9SM | 5.1            | 10.8     | 0.201      | 0.425      |
| PWT2514035*4SM | PWT2514035*9SM | 4.5            | 5.1      | 0.177      | 0.201      |
| PWT2519076*4SM | PWT2519076*9SM | 6.0            | 16.6     | 0.236      | 0.654      |
| PWT2525140D4SM | PWT2525140*9SM | 8.0            | 35.0     | 0.315      | 1.378      |
| PWT3225093*4SM | PWT3225093D4SM | 8.0            | 20.1     | 0.315      | 0.791      |

\*) Core diameter (D=38mm, B=76mm)

## RELATED PRODUCTS



MK10 printers

