



INFORMATION

- + Diesel Resistant
- + Meets SNCF Spec. NF-F00-608
- + Meets SAE-AMS-DTL-23053-6 Class 1
- + Meets UL 125C, 300V
- + Print Performance to Military Standards
- + Ladder format
- + Supplied widths 12.5mm - 25mm - 50mm
- + Colours - white and yellow

SPECIFICATIONS

Temperature range

-55°C to +135°C

Material

radiation cross linked UV stabilised and printable polyolefin

Print

thermal transfer

Print performance

Adherence: SAE-AS81531-1998 Clause 4.6.2

Fluid Resistance: MIL202 Method 215J

Standard colours

yellow and white

Shrink ratio

3:1

Certified and issued to:

SNCF NF F00-608

SAE-AMS-DTL-23053/6

DIMENSIONS | PACKAGING

TYPE	DIAMETER (D mm)	DIAMETER (D1 mm)	SLEEVE LENGTH (mm)	MARKERS ACCROSS	MARKERS / BOX
NF^032125LR*	3.2	110	12.5	4	4000
NF^032250LR*	3.2	110	25	2	2000
NF^032500LR*	3.2	110	50	1	1000
NF^048125LR*	4.8	16	12.5	4	4000
NF^048250LR*	4.8	16	25	2	2000
NF^048500LR*	4.8	16	50	1	1000
NF^064125LR*	6.4	210	12.5	4	4000
NF^064250LR*	6.4	210	25	2	2000
NF^064500LR*	6.4	210	50	1	1000
NF^095125LR*	9.5	3.2	12.5	4	2000
NF^095250LR*	9.5	3.2	25	2	1000
NF^095500LR*	9.5	3.2	50	1	500
NF^127125LR*	12.7	4.2	12.5	4	2000
NF^127250LR*	12.7	4.2	25	2	1000
NF^127500LR*	12.7	4.2	50	1	500
NF^180125LR*	18.0	6.4	12.5	4	2000
NF^180250LR*	18.0	6.4	25	2	1000
NF^180500LR*	18.0	6.4	50	1	500
NF^254250LR*	25.4	8.5	12.5	4	1200
NF^254500LR*	25.4	8.5	25	2	600
NF^381500LR*	25.4	8.5	50	1	300

^ = S (single sided), D (double sided)

* = Colour (4=Yellow, 9=White)