



INFORMATION

- + Flame Retardant
- + Self Extinguishing
- + Meets SAE-AMS-DTL 23053/18 Specification
- + Flame Retardant to UL224 VW-1
- + Print onto Paper Liner for QA
- + Backwards compatible for most printers
- + Perforation after every sleeve for easy sorting
- + Print performance to Military Specifications

SPECIFICATIONS

Temperature range

-55°C to +225°C

Material

high temperature rated, flexible, highly flame retardant, polyvinylidene fluoride printable sleeves

Print

thermal transfer

Print performance

Adherence: SAE-AS5942

Fluid Resistance: MIL202 Method 215J

Standard colours

white

Shrink ratio

2:1

Certified and issued to:

UL224 VW-1 Flammability

SAE-AMS-DTL-23053/18

DIMENSIONS | PACKAGING

TYPE	DIAMETER (D mm)	DIAMETER (D1 mm)	SLEEVE LENGTH (mm)	MARKERS ACCROSS	MARKERS / BOX
ET^024125LR9	2.4	12	12.5	4	4000
ET^024250LR9	2.4	12	25	2	2000
ET^024500LR9	2.4	12	50	1	1000
ET^032125LR9	3.2	16	12.5	4	4000
ET^032250LR9	3.2	16	25	2	2000
ET^032500LR9	3.2	16	50	1	1000
ET^048125LR9	4.8	24	12.5	4	4000
ET^048250LR9	4.8	24	25	2	2000
ET^048500LR9	4.8	24	50	1	1000
ET^064125LR9	6.4	32	12.5	4	4000
ET^064250LR9	6.4	32	25	2	2000
ET^064500LR9	6.4	32	50	1	1000
ET^095125LR9	9.5	4.75	12.5	4	2000
ET^095250LR9	9.5	4.75	25	2	1000
ET^095500LR9	9.5	4.75	50	1	500
ET^127125LR9	12.7	6.4	12.5	4	2000
ET^127250LR9	12.7	6.4	25	2	1000
ET^127500LR9	12.7	6.4	50	1	500
ET^180125LR9	19.1	9.5	12.5	4	2000
ET^180250LR9	19.1	9.5	25	2	1000
ET^180500LR9	19.1	9.5	50	1	500
ET^254125LR9	25.4	12.7	12.5	4	1200
ET^254250LR9	25.4	12.7	25	2	600
ET^254500LR9	25.4	12.7	50	1	300
ET^381500LR9	38.1	19.1	50	1	100

^ = S (single sided), D (double sided)