



INFORMATION

- + Flame retardant
- + Self extinguishing ladder format
- + UL224 VW-1 Flammability
- + Supplied widths 12.5mm - 25mm - 50mm
- + Colours - white and yellow

SPECIFICATIONS

Temperature range
-55°C to +125°C

Material
flexible polyolefin

Print
thermal transfer

Standard colours
yellow and white

Shrink ratio
2:1

Certified and issued to:
BS 6746 C
UL224 VW-1 Flammability
International RCC Markers
MIL-I-23053/5
SAE-AMS-DTL-23053/5

DIMENSIONS | PACKAGING

TYPE	DIAMETER [D mm]	DIAMETER [D1 mm]	SLEEVE LENGTH [mm]	MARKERS ACCROSS	MARKERS / BOX
SG^012125LR*	12	0.6	12.5	4	4000
SG^012250LR*	12	0.6	25	2	2000
SG^012500LR*	12	0.6	50	1	1000
SG^016125LR*	16	0.8	12.5	4	4000
SG^016250LR*	16	0.8	25	2	2000
SG^016500LR*	16	0.8	50	1	1000
SG^024125LR*	2.4	12	12.5	4	4000
SG^024250LR*	2.4	12	25	2	2000
SG^024500LR*	2.4	12	50	1	1000
SG^032125LR*	3.2	16	12.5	4	4000
SG^032250LR*	3.2	16	25	2	2000
SG^032500LR*	3.2	16	50	1	1000
SG^048125LR*	4.8	2.4	12.5	4	4000
SG^048250LR*	4.8	2.4	25	2	2000
SG^048500LR*	4.8	2.4	50	1	1000
SG^064125LR*	6.4	3.2	12.5	4	4000
SG^064250LR*	6.4	3.2	25	2	2000
SG^064500LR*	6.4	3.2	50	1	1000
SG^095125LR*	9.5	3.2	12.5	4	2000
SG^095250LR*	9.5	3.2	25	2	1000
SG^095500LR*	9.5	3.2	50	1	500
SG^127125LR*	12.7	4.8	12.5	4	2000
SG^127250LR*	12.7	4.8	25	2	1000
SG^127500LR*	12.7	4.8	50	1	500
SG^180125LR*	19.1	9.5	12.5	4	2000
SG^180250LR*	19.1	9.5	25	2	1000
SG^180500LR*	19.1	9.5	50	1	500
SG^254250LR*	25.4	12.7	12.5	4	1200
SG^254500LR*	25.4	12.7	25	2	600
SG^381500LR*	25.4	12.7	50	1	300

^ = S (single sided), D (double sided)

* = Colour (4=Yellow, 9=White)