



SINGLE-CHARACTER MARKING



PY WIRE MARKING

- Closed secure combination marker sleeve for smaller diameter wires.
- Flexible sleeve profile, covers wide diameter areas and allows rapid installation.
- Large surface with excellent readability.



GENERAL INFORMATION

Design

Closed combination marker. A special Y-shaped profile covers a wide diameter range of small wires. The large print surface of the marker enables excelent readability in normal reading distances.

Material

Cadmium and silicon free soft PVC in accordance with Partex formula.

Colours

Standard colours yellow and white and international colour code for 0-9.

Print

Hot stamped.

Text

Alphanumerical and special characters.

Multi-character marking

Can also be delivered as customized multi character marking. Especially suitable in telecom and PLC applications. See separate product information.

FACTS

Temperature range

Shape permanent between $-30^{\circ}C$ and $+60^{\circ}C$ ($-22^{\circ}F$ and $+140^{\circ}F$).

Resistance

The product is tested according to Partex Product Test Programme by the Swedish Test and Research Institute and has the following test properties:

- Flammability resistance according to UL94-V0.
- Resistant to UV radiation, corresponding to 1 year outdoors in the south of Sweden.
- Resistance to chemicals meets Partex Product Test Programme.
- Resistance to temperature and ageing meets norms of Partex Product Test Programme.

For application in hostile environments, please contact Partex for information.

DIMENSIONS IN MM (NOMINAL)

Type designation	Height (H)	Width (B)	Text height
PY-01	3.3	3.5	2.6



SIZES AND PACKAGING

Article number	Application range	Length	Number of	Semi cut	Loose, cut
	Diameter/Area/Inch	mm	characters	marker sleeves	marker sleeves
PY-01003*V×&.#	~ 1.0 - 2.0 MM ~ 0.2 - 0.7 MM ² .039"079"	3	1	Reel 1000 pcs	Strip pack 1000 pcs, (5X200)

* = Packaging. A = Cut markers B= 1000-reel P = Marker strips
V = Hot stamped.
x = Sleeve colour according to the international colour code.
& = Character colour black or white. For other colours, please contact Partex.
= Character.

N.B! If you wish neutral/blank markers, please exchange the letter ${\sf *V}{\sf «}$ to ${\sf *N}{\sf «}.$

APPLICATION

