



+ INFORMATION

- + Compact, fast and portable printer to cover most of your marker needs.
- + Easy to operate with Partex product menu.
- + Feeds, prints and cuts bulk Partex profiles and self adhesive labels.
- + Store and import markerfiles with a USB - PC connection.
- + Cost effective identification system for use in panel building and electrical installations.

+ PROPERTIES

Temperature range

Operating temperature: +15°C - +32,5°C

Operating temperature with pre-heater: from +5°C

Storage temperature: +5°C - +35°C

To obtain the best printing result, the temperature of the profile shouldn't be lower then: +20°C

Thermal transfer printing

300 dpi print resolution

Printing speed

18.5 mm/s - low speed mode

25 mm/s - standard mode

40 mm/s - high speed mode

Text heights

1.3, 2, 3, 4 or 6mm

Maximum rows that can be printed:

1-3 rows

PC connection

USB 2.0 and Partex software Promark Creator

Internal Memory

15000 characters

Number of characters to be sent to PC

No limits with Promark Creator T-1000

Power

Power Supply 100 ~ 240 V AC (50 ~ 60 Hz)

Power: 13 W

Certified with CE mark

Dimensions

(L x W x H): 250 x 300 x 85 mm

Weight

2 kg

+ KIT CONTENTS

- + PROMARK T-1000, soft carrying case,
- + AC adapter, power cord,
- + Ink ribbon, black, 40 m,
- + Profile guide
- + USB cable,
- + software,

+ SPECIFICATION

- + ProMark T1000 is a successor to our most popular profile printer the T800. Complemented with new options, such as Polish and Russian font, and menu with Partex article numbers, is a perfect solution for installers and producers of control cabinets and panel boards.
- + Low weight, small size, as well as inbuilt memory allow you to operate the printer on site. The library of electrical symbols enables you to print objects such as Ω , etc.
- + An additional asset will be the menu with Partex products indexes. After selecting the type of a profile, T-1000 will automatically choose the position of text and the depth of the cut.
- + The backlit display and QWERTY keyboard allows entering additional symbols very quickly. The advanced projects can be sent to T-1000 via the new, English version of WinSign software, which enables you to import Excel files with the "copy and paste" function.

+ PROFILES TO PRINT


- + PO and POZ profiles with diameters of 1.3 – 5.5 mm (POZ is the halogen-free version)
- + PHZ – round, halogen-free, heat shrinkable tubes with diameters 2.4 – 6.4 mm before shrinking
- + PHZF – flat, halogen-free, heat shrinkable tubes with diameters 2.4 – 6.4 mm before shrinking
- + PP+ profile – height of 4.6 and 9.0 mm compatible with profiles: PT+/PTC/PTZ and PM, PTM, PS
- + PP+ profile – height of 6.3, 10.0 and 11.0 mm compatible with Wago connectors (TopJobs), Phoenix Contact, ABB Entrellec.
- + PPA+ – self-adhesive profile
- + PO-068 profile – used for marking cables with PKH and POH holders
- + PROMARK-PLL – self laminating marker for wires and cables
- + PROMARK-PL – adhesive tape with a width of 6mm, 9mm and 12mm available in the form of cassettes which you place into the printer

+ ACCESSORIES

TYPE	DESCRIPTION
PROMARK-RB-BLACK	black ribbon 100 m
PROMARK-RB-WHITE	white ribbon 85 m
PROMARK-CU	cutting unit
PROMARK-TA	tube attachment
PROMARK-TA-CLEAN	cleaning kit guide for tube attachment (3 pcs)
PROMARK-PA	plate attachment
PROMARK-PA-CLEAN	cleaning kit guide for plate attachment (3 pcs)
PROMARK-TW	profile warmer
PROMARK-TW-CLEAN	cleaning kit guide for the profile warmer (3 pcs)
PROMARK-AF	profile feeder
PROMARK-HC	aluminium case
MK-STV	reel stand
MK-RS3	small reel stand



MK-STV



MK-RS3



PROMARK-HC

+ RELATED PRODUCTS



Promark Creator

▶ PAGE 126

+ PO-PROFILE

TYPE	HALOGEN FREE VERSION	DIAMETER [mm] [min/max]	CROSS SECTIONAL AREA [mm²]	PACKAGING
P0-01	POZ01	1.3/1.8	0.25	6 m / 250 m
P0-02	POZ02	1.7/2.2	0.5	5 m / 60 m / 250 m
P0-03	POZ03	2.0/2.5	0.75	4.5 m / 50 m / 250 m
P0-04	POZ04	2.2/2.8	1.0	4.5 m / 50 m / 200 m
P0-05	POZ05	2.7/3.5	1.5	4 m / 40 m / 200 m
P0-06	POZ06	3.2/4.0	2.5	3.5 m / 40 m / 200 m
P0-06Q**	-	-	-	3.5 m / 40 m
P0-068Q**	PKZ20Q	-	-	25 m / 50 m
P0-068TW	PKZ20	6.8/7.0	-	4.5 m / 50 m
P0-07	POZ07	3.8/4.7	4.0	3.5 m / 30 m / 100 m
P0-08	POZ08	4.6/5.5	6.0	3 m / 30 m / 100 m



P0/POZ
▶ PAGE 28



P0-068
▶ PAGE 28

STANDARD COLOUR: yellow, white. Others on request. * Mounting with marker holder POH or PKH ** Mounting with cable tie

+ HEATSHRINKABLE TUBES PHZ

TYPE	DIAMETER BEFORE SHRINKING [mm]	DIAMETER AFTER SHRINKING [mm]	PACKAGING
PHZ20024	2.4	1.2	15 m or 100 m
PHZ20032	3.2	1.6	15 m or 100 m
PHZ20048	4.8	2.4	12 m or 100 m
PHZ20064	6.4	3.2	12 m or 100 m



PHZ
▶ PAGE 32

STANDARD COLOURS: yellow, white. Other on request.

+ FLAT HEATSHRINKABLE TUBES PHZF

TYPE	DIAMETER BEFORE SHRINKING [mm]	DIAMETER AFTER SHRINKING [mm]	PACKAGING
PHZF20024	2.4	1.2	100 m / 25 m
PHZF20032	3.2	1.6	100 m / 25 m
PHZF20048	4.8	2.4	100 m / 25 m
PHZF20064	6.4	3.2	100 m / 25 m



PHZF
▶ PAGE 34

STANDARD COLOURS: yellow, white. Other on request.



+

PP+ PROFILE


TYPE	HEIGHT [mm]	FIT FOR	PACKAGING
PP+046	4.6	PT+, PTC, PTZ, PM-10	50 m / 17 m
PP+063	6.3	terminals Phoenix Contact *	50 m / 17 m
PP+09	9.0	PM-20, PS	50 m / 17 m
PP+100	10.2	terminals ABB Entelec	50 m / 17 m
PP+110	11.0	terminals Wago (TopJobs)	50 m / 17 m
PPA+09	9.0	components	20 m / 10 m

STANDARD COLOURS: yellow, white * UT2.5, UTTB2.5, ST4, DT2.5, QTC, DTI2.5



PT+

▶ PAGE 48



PTC

▶ PAGE 50



PM

▶ PAGE 52



PS

▶ PAGE 82



PPA+

▶ PAGE 84



PP+

▶ PAGE 84

+

SELF SDHESIVE LABELS

TYPE	HEIGHT [mm]	COLOUR	LENGTH [m]	PACKAGING
PROMARK-PL060	6	yellow, white silver	30	1 cassette
			30	
			27	
PROMARK-PL090	9	yellow, white silver	30	1 cassette
			30	
			27	
PROMARK-PL120	12	yellow, white silver	30	1 cassette
			30	
			27	
PROMARK-PLL33	33 (printable area 10)	white	8	1 cassette



PROMARK-PL



PROMARK-PLL

