

PROMARK

MARKING MACHINE T-1000

- Compact, fast and portable printer to cover most of your marker needs.
- Easy to operate with Partex pre-installed profile menu.
- Feeds, prints and cuts bulk Partex profiles and self adhesive labels.
- Store and import markerfiles with a USB - PC connection.
- Cost effective identification system for use in panel building and electrical installations.



GENERAL INFORMATION

Design

ProMark T-1000 is the latest addition to the ProMark family. It is an upgrade of our most popular profile printer ProMark T-800.

Its menu is now available in English, Swedish, German, Polish, French, Spanish, Portuguese and Russian languages. T-1000 has also got an expanded symbol library.

Complemented with the the new features, and menu with Partex tubing types and sizes, is it a perfect solution for installers and producers of control panels.

The backlit display and QWERTY keyboard allows entering additional symbols very quickly.

The advanced projects can be sent to T-1000 via the new WinSign software, which enables you to import Excel files with the "copy and paste" function.

Features

- High production speed
- High quality thermotransfer print
- Menu with Partex products to ensure the right settings
- USB-connection to PC
- Partex software WinSign T-1000

FACTS

Thermal transfer printing

300 dpi print resolution

Printing speed

40.0 mm/s in high speed mode

25.0 mm/s

18.5 mm/s in low speed mode

Text heights

1.3, 2.0, 3.0, 4.0 or 6.0mm

Maximum rows that can be printed

1-3 rows

PC connection

USB 2.0 and Partex software WinSign

Power

AC adapter 100 ~ 240V (50-60Hz)

Power consumption: 13 W

CE-certified

Measurement

(LxWxH) 250x300x85

Weight

2kg

Temperature range:

Operating temperature: +15°C to +32,5°C

Operating temperature with pre-heater: from +5°C

Storage temperature: 5°C to +35°C

To obtain the best printing result, the temperature of the profile shouldn't be lower then +20°C

THE PROMARK CONCEPT



T-1000



T-1000 prints on Partex profiles. Choose which profile you are printing on and the machine adjusts cutting depth and print position.



T-1000 is delivered with a reel stand for SN- and DN-reels.



T-1000 is delivered in a soft case



It is possibility to upgrade to a hard aluminium case to ensure safe transportation of the machine.



Profile cleaner.

APPLICATIONS



Compacta disc with PP+ profile



PP+ profile mounted on blocks



PP+ profile in PTC sleeve



T-1000 also print great on labels



PP+ profile in PT+ sleeve




PO-068TW on POH



Compactdisc with PO-profile



PO-068Q-profile



PO-profile on DN-reel

PRODUCT AND ORDERING INFORMATION

Article number	Information	Pack unit (MOQ)
Machine and accessories		
T1000-PROMARK-KIT1	PROMARK T-1000 printer, black starting ribbon, (40m), tube attachment, AC adapter, power cable, USB cable, software, soft carrying case, PO-068TWSN4, PO-05000SN4, reel stand MKRS3	BOX
T1000-RB-BLACK	black ribbon 100 m	5 pcs 500 m
T1000-RB-WHITE	white ribbon 85 m	5 pcs 425 m
T1000-CU	cutting unit	1 pcs
T1000-TA	tube attachment	1 pce
T1000-TA-CLEAN	cleaning kit guide for tube attachment (3 pcs)	1 pce
T1000-PA	plate attachment	1 pce
T1000-PA-CLEAN	cleaning kit guide for plate attachment (3 pcs)	1 pce
T1000-TW	profile warmer	1 pce
T1000-TW-CLEAN	Cleaning kit guide for the profiles heater (3 pcs)	1 pce
T1000-AF	profile feeder	1 pce
T1000-HC	aluminium case	1 pce
MK-RS3	reel stand	1 pce
Tapes		
T1000-PL060CN*	6 mm x 30 m	1 pcs
T1000-PL090CN*	9 mm x 30 m	1 pcs
T1000-PL120CN*	12 mm x 30 m	1 pcs
T1000-PL060CN8	6 mm x 27 mm silver	1 pcs
T1000-PL090CN8	9 mm x 27 mm silver	1 pcs
T1000-PL120CN8	12 mm x 27 mm silver	1 pcs
T1000-PLL33CN9	33 mm x 8 m white - self-laminating label (wrap-around)	1 pcs
Wire markers		
PO-01000SNx	PO-profile 0,25mm ² . Diam 1,3-1,8mm	6,0m / Compactadisc
PO-01000DNx	PO-profile 0,25mm ² . Diam 1,3-1,8mm	60,0m / DN-reel
PO-01000BNx	PO-profile 0,25mm ² . Diam 1,3-1,8mm	250,0 / BN-reel
PO-02000SNx	PO-profile 0,5mm ² . Diam 1,7-2,2mm	5,0m / Compactadisc
PO-02000DNx	PO-profile 0,5mm ² . Diam 1,7-2,2mm	60,0m / DN-reel
PO-02000BNx	PO-profile 0,5mm ² . Diam 1,7-2,2mm	250,0 / BN-reel
PO-03000SNx	PO-profile 0,75mm ² Diam 2,0-2,5mm	4,5m / Compactadisc
PO-03000DNx	PO-profile 0,75mm ² Diam 2,0-2,5mm	50,0m / DN-reel
PO-03000BNx	PO-profile 0,75mm ² Diam 2,0-2,5mm	250,0 / BN-reel
PO-04000SNx	PO-profile 1,0mm ² Diam 2,2-2,8mm	4,5m / Compactadisc
PO-04000DNx	PO-profile 1,0mm ² Diam 2,2-2,8mm	50,0m / DN-reel
PO-04000BNx	PO-profile 1,0mm ² Diam 2,2-2,8mm	250,0 / BN-reel
PO-05000SNx	PO-profile 1,5mm ² Diam 2,7-3,5mm	4,0m / Compactadisc
PO-05000DNx	PO-profile 1,5mm ² Diam 2,7-3,5mm	40,0m / DN-reel
PO-05000BNx	PO-profile 1,5mm ² Diam 2,7-3,5mm	200,0 / BN-reel
PO-06000SNx	PO-profile 2,5mm ² Diam 3,2-4,0mm	3,5m / Compactadisc
PO-06000DNx	PO-profile 2,5mm ² Diam 3,2-4,0mm	40,0m / DN-reel
PO-06000BNx	PO-profile 2,5mm ² Diam 3,2-4,0mm	200,0 / BN-reel
PO-068TWBNx	PO-068TW profile with thin wall Diam 6,8-7,0 mm	50,0m / BN-reel
PO-068TWDNx	PO-068TW profile with thin wall Diam 6,8-7,0 mm	25,0m / DN-reel
PO-068TWSNx	PO-068TW profile with thin wall Diam 6,8-7,0 mm	4,5m / Compactadisc

PO-07000SNx	PO-profile 4,0mm ² Diam 3,8-4,7mm	3,5m / Compactadisc
PO-07000DNx	PO-profile 4,0mm ² Diam 3,8-4,7mm	30,0m / DN-reel
PO-07000BNx	PO-profil 4,0mm ² Diam 3,8-4,7mm	100,0m / BN-rulle
PO-08000SNx	PO-profile 6,0mm ² Diam 4,6-5,5mm	3,0m / SN-reel
PO-08000DNx	PO-profile 6,0mm ² Diam 4,6-5,5mm	30,0m / DN-reel
PO-08000BNx	PO-profil 6,0mm ² Diam 4,6-5,5mm	100,0m / BN-reel
POZ01000SNx	POZ-profile 0,25mm ² . Diam 1,3-1,8mm	6,0m / Compactadisc
POZ01000DNx	POZ-profile 0,25mm ² . Diam 1,3-1,8mm	60,0m / DN-reel
POZ02000SNx	POZ-profile 0,5mm ² . Diam 1,7-2,2mm	5,0m / Compactadisc
POZ02000DNx	POZ-profile 0,5mm ² . Diam 1,7-2,2mm	60,0m / DN-reel
POZ03000SNx	POZ-profile 0,75mm ² . Diam 2,0-2,5mm	4,5m / Compactadisc
POZ03000DNx	POZ-profile 0,75mm ² . Diam 2,0-2,5mm	50,0m / DN-reel
POZ04000SNx	POZ-profile 1,0mm ² . Diam 2,2-2,8mm	4,5m / Compactadisc
POZ04000DNx	POZ-profile 1,0mm ² . Diam 2,2-2,8mm	50,0m / DN-reel
POZ05000SNx	POZ-profile 1,5mm ² . Diam 2,7-3,5mm	4,0m / Compactadisc
POZ05000DNx	POZ-profile 1,5mm ² . Diam 2,7-3,5mm	40,0m / DN-reel
POZ06000SNx	POZ-profile 2,5mm ² . Diam 3,2-4,0mm	3,5m / Compactadisc
POZ06000DNx	POZ-profile 2,5mm ² . Diam 3,2-4,0mm	40,0m / DN-reel
POZ07000SNx	POZ-profile 4,0mm ² . Diam 3,8-4,7mm	3,5m / Compactadisc
POZ07000DNx	POZ-profile 4,0mm ² . Diam 3,8-4,7mm	30,0m / DN-reel
POZ08000SNx	POZ-profile 6,0mm ² . Diam 4,6-5,5mm	3,5m / Compactadisc
POZ08000DNx	POZ-profile 6,0mm ² . Diam 4,6-5,5mm	30,0m / DN-reel
Marker tag profile		
PP+04600SNx	PP-profile H=4,6mm, fit PT+ and PM-10	17,0m / Compactadisc
PP+04600DNx	PP-profile H=4.6 mm	50,0m / DN-reel
PP-09000SNx	PP-profile H=9,0mm, fit PM-20	17,0m / Compactadisc
PP-09000DNx	PP-profile H=9,0mm, fit PM-20	50,0m / DN-reel
Cabinet and Component markers		
PP+04600SNx	PP+profil H=4,6 mm, for PT+, PTC, PM and PTM	17,0m / Compactadisc
PP+04600DNx	PP+profil H=4,6 mm, for PT+, PTC, PM and PTM	50,0m / DN-reel
PP+06300SNx	PP-profile H=6.3 mm, for Phoenix terminal blocks (UT2.5, UTTB2.5, ST4, DT2.5, QTC, DTI2.5)	17,0m / Compactadisc
PP+06300DNx	PP-profile H=6.3 mm, for Phoenix terminal blocks (UT2.5, UTTB2.5, ST4, DT2.5, QTC, DTI2.5)	50,0m / DN-reel
PP+09000SNx	PP+profile H=9,0 mm, for PM	17,0m / Compactadisc
PP+09000DNx	PP+profile H=9,0 mm, for PM	50,0m / DN-reel
PP+10000SNx	PP+profile H=10.2 mm, for Entrelecs terminal blocks	17,0m / Compactadisc
PP+10000DNx	PP+profile H=10.2 mm, for Entrelecs terminal blocks	50,0m / DN-reel
PP+11000SNx	PP+profile H=11.0 mm, for Wagos TopJobs terminal blocks	17,0m / Compactadisc
PP+11000DNx	PP+profile H=11.0 mm, for Wagos TopJobs terminal blocks	50,0m / DN-reel
PPA+09000SNx	PP + profile with adhesive for component marking etc. H=9,0 mm	10,0m / Compactadisc
PPA+09000DNx	PP + profile with adhesive for component marking etc. H=9,0 mm	25,0m / DN-reel
Heat shrink tubing		
PHZ20032MNx	Heat Shrink , Diam 3.2mm, shrink ration 2:1, Zerex	15,0m / Minibox
PHZ20048MNx	Heat Shrink, Diam 4,8mm, okrympt shrink ration 2:1, Zerex	12,0m / Minibox
PHZ20064MNx	Heat Shrink, Diam 6,4mm, okrympt shrink ration 2:1, Zerex	12,0m / Minibox
PHZF20024^N*	Flat Heat Shrink 2.4 mm, shrink ration 2:1, ZEREX	25 m / 100 m
PHZF20032^N*	Flat Heat Shrink 3.2 mm, shrink ration 2:1, ZEREX	25 m / 100 m
PHZF20048^N*	Flat Heat Shrink 4.8 mm, shrink ration 2:1, ZEREX	25 m / 100 m
PHZF20064^N*	Flat Heat Shrink 6.4 mm, shrink ration 2:1, ZEREX	25 m / 100 m
Cable markers		
PKZ20DNx	PKZ 2 profile Zerex	20m / DN-reel
PKZ20Q10DNx	PKZ 2 profile Zerex, punched, 10mm between punched holes	20m / DN-reel
PO-068Q10BNx	PO-068Q profile punched, 10mm between the punched holes	50,0m / BN-reel
PO-068Q10DNx	PO-068Q profile punched, 10mm between the punched holes	25,0m / DN-reel
PO-06Q10SN*	PO-06Q profile punched	3,5 m / SN-reel
PO-06Q10DN*	PO-06Q profile punched	40 m / DN-reel
POZ06Q10SN*	POZ-06Q profile punched	3,5 m / SN-reel

x = 4 yellow profile ; 9 white profile ; other colours on request Zerex = Halogen free ^ = B big reel ; S small reel

Notes: Sleeves and Carrier strips Zerex = Halogen free

Following Partex products are possible to combine with the ProMark consumables:

- PM-10/20/24 transparent sleeves with ProMark PP-046/090 insert tags and T1000-PL090/120 self adhesive labels.
- PT+02/10/20/30 transparent sleeves combined with PP-046 insert tag profile.

- PTC10/20/30/50 transparent sleeves are combined with PP-046 insert tag profile

- PKH and POH carrier strips are combined with PO-068TW / PRZ071 cable marking profiles.

- PP-09 and T1000-PL are combined with PS.

For detailed information, see separate data sheet.